bar	Rotating						
bar	Oscillating						
bar	Fixed						
Temper	ature °C -						

à

0







<section-header><section-header><text><text></text></text></section-header></section-header>															
Should you have any doubts about the choice of sealing	Туре	FMP 500	FMP 500M	FMP 501	FMP 502	FMP 403	FMP 404 (S)	FMP 404	FMP 507	FMP 506	FMP 509	FMP 510	FMP 524	FMP 702	FMP 702M
material, please refer to us, Our Engineering cell will be happy to assist you.	Fiber	Expanded Graphite	Graphite+ Inconel Wire	Carbon Filament	PTFE G. Filament	PTFE Graphited	PTFE White Dry	PTFE Silicon	PTFE+ Graphite	Aramid Silicon	Aramid+ Graphite	Aramid+ PTFE	Glass Fiber	Ceramic Fiber	Ceramic+ S.S. Wire
bar Rotating		30	30	35	20	35	25	35	35	35	20	35			
bar Oscillating		100	150	100	150	100	-	100	100	100	80	150			
bar Fixed		300	350	350	250	200	100	200	200	200	150	200	150	300	300
Temperature °C -		-240	-240	-200	-240	-200	-100	-200	-200	-200	-100	-100		-200	-200
Temperature °C + Temperature °C steam		+450	+450	+600	+200	+280	+280	+280	+280	+280	+280	+290	+550	1100	1100
		+650	+650	+600	+280	-		-	-	-	-	-	-	1000	1000
	рН	0-14	0-14	0-14	0-14	0-12	0-14	0-14	0-14	2-12	2-12	1-13	4-13	0-14	1-14
Density	g/cm³	1.0	1.0	1.1	1.5	1.55	1.5	1.6	1.6	1.5	1.5	1.5	1.5	0.64	1.00
Water															
Steam															
Neutral Solutions															
Dilute Acids															
Mild Acids		•						0							•
Concentrated Acids		•		•											
Dilute Alkalies															
Strong Alkalies															
Inert Gases															
Acidic Vapours/Gases Solvents															
Organic Compounds															
Mineral Oil															
Synthetic Oil															
Abrasive Media															
Bitumen															
Lacqures															
	Legends:	Suitable	Conditional Suitable												

AII DATA QUOTED ABOVE ARE BASED ON YEARS OF EXPERIENCE IN PRODUCTION & OPERATION OF SEALING ELEMENTS, IN VIEW OF THE WIDE VARIETY OF POSSIBLE INSTALLATION & OPERATING CONDITIONS ONE CAN NOT THEREFORE, BE USED TO SUPPORT ANY WARRANTY CLAIMS. WHENEVER THERE IS ANY DOUBT, OUR STAFF WILL BE PLEASED TO ASSIST YOU IN FINDING THE OPTIMUM SEALING SOLUTIONS.











